

GUANTES AISLANTES DE CAUCHO NOVAX

FICHA TÉCNICA	Protección de Manos
    	1. Guantes Dielectrico.
	2. Descripción: El guante, fabricado en caucho natural, ofrece las propiedades dieléctricas requeridas, combinado con flexibilidad, fuerza y durabilidad. La forma contorneada reduce la fatiga de la mano. Los guantes de electricista NOVAX son probados individualmente para respetar las directrices ANSI/ASTM D120 Estándar y NFPA 70. E Y Usarlos en zonas de riesgo eléctrico y para electro soldadura. Usos: generación de potencia, contratistas eléctricos, mantenimiento de planta industrial reparación de automotor
	3. Especificación: • Marca: NOVAX • Procedencia: MALASYA
	4. Certificaciones EN60903 ,ASTM D120 , NFPA 70E,29CFR part 1910- Occupational Safety and Health Standards ASTM D 120-02a- Rubber Insulating GlovesASTM- F496-06- In-Services Care of Insulating Gloves and SleevesASTM F696-02- Leather Protectors for Rubber Insulating Gloves and Mitt ASTM F1236-96- Visual Inspection of Electrical Protective Rubber Products.

Clase	Longitud	Tallas	Marca	Espesor	Standard	T.Prueba	T.Uso
00	11"	7,8,9,10,11	NOVAX	0.75	EN60903 ASTM D120 NFPA 70E	2,500 V	500 V
0	11"	7,8,9,10,11	NOVAX	1.0	EN60903 ASTM D120 NFPA 70E	5,000 V	1,000V
1	14	7,8,9,10,11	NOVAX	1.5	EN60903 ASTM D120 NFPA 70E	10,000 V	7,5000V
2	14"	7,8,9,10,11	NOVAX	2.3	EN60903 ASTM D120 NFPA 70E	20,000 V	17,000 V
3	14"	9,10,11,12	NOVAX	2.9	EN60903 ASTM D120 NFPA 70E	30,000 V	26,500 V
4	14"	7,8,9,10,11	NOVAX	2.3	EN60903 ASTM D120 NFPA 70E	40,000 V	36,000 V

ASTM D120 - Especificación estándar para guantes aislantes de goma

Nuestros guantes están etiquetados según las especificaciones según la tabla a continuación:

CLASS COLOR:	PROOF TEST VOLTAGE AC/DC:	PROOF TEST VOLTAGE AC/DC:	GLOVE LABEL:
00 BEIGE	2,500 / 10,000	500 / 750*	
0 RED	5,000 / 20,000	1,000 / 1,500*	
1 WHITE	10,000 / 40,000	7,500 / 11,250*	
2 YELLOW	20,000 / 50,000	17,000 / 25,500*	
3 GREEN	30,000 / 60,000	26,500 / 39,750*	
4 ORANGE	40,000 / 70,000	36,000 / 54,000*	

description	cuff style	colour						length		sizes
								mm	inch	
NOVAX CLASS 00 2,500 Volt Tested 500 Volt Working	Straight Straight	*	*	*	*			280 360	11 14	7•8•9•10•11•12 7•8•9•10•11•12
NOVAX CLASS 0 5,000 Volt Tested 1,000 Volt Working	Straight Straight	*	*	*	*	*	*	280 360	11 14	7•8•9•10•11•12 7•8•9•10•11•12
NOVAX CLASS 1 10,000 Volt Tested 7,500 Volt Working	Straight Contour Bell	*	*	*	*	*	*	360 460 460	14 18 18	7•8•9•10•11•12 8•9•10•11•12 9•10•11•12
NOVAX CLASS 2 20,000 Volt Tested 17,000 Volt Working	Straight Contour Bell	*	*	*	*	*	*	360 460 460	14 18 18	7•8•9•10•11•12 8•9•10•11•12 9•10•11•12
NOVAX CLASS 3 30,000 Volt Tested 26,500 Volt Working	Straight Straight Contour Bell	*	*		*	*	*	410 460 460 460	16 18 18 18	9•10•11•12 9•10•11•12 9•10•11•12 9•10•11•12
NOVAX CLASS 4 40,000 Volt Tested 36,000 Volt Working	Straight Straight Contour Bell	*	*		*	*	*	410 460 460 460	16 18 18 18	9•10•11•12 9•10•11•12 9•10•11•12 9•10•11•12

The contoured shape & softness reduces hand fatigue.
Every single NOVAX Glove is tested, inspected and packed according to the requirements in ASTM D120 and EN 60903.
The gloves are numbered individually for traceability and stamped with the factory manufacturing date by ink stamp.

orange black red yellow orange/black red/black

varorange/black